











Digital Manufacturing Laboratory – 118 Bonner Hall – Additive Manufacturing / 3D Printing Resources

Image	Item	Material	Build Volume (W/D/H) Layer Thickness / Resolution	File Formats	General Features
<b>Fused Deposition Modeling: FDM Printers (desktop)</b>					
	<b>MakerBot Replicator (5th Generation)</b>	<b>Plastic:</b> Polylactic Acid (PLA)	<b>Build Volume:</b> 9.9 x 7.8 x 5.9 inches (25.2 x 19.9 x 15.0 cm) <b>Layer Thickness:</b> 100 microns (0.0039 in)	STL, OBJ, THING, MAKERBOT	<ul style="list-style-type: none"> <li>• Creates professional-quality, high-resolution prototypes and complex models</li> <li>• Software auto-generates supports; minimal support removal and sanding required</li> <li>• Choose settings that range from fast draft to finer resolution</li> </ul>
	<b>Original Prusa i3 MK3S+</b>	<b>Various (not all in stock):</b> PLA, ABS, PET/PETG, HIPS, Flex PP, Ninjaflex, Laywood, Laybrick, Nylon, Bamboofill, Bronzefill, ASA, T-Glase, Carbon-fibers enhanced filaments, Polycarbonates	<b>Build Volume:</b> 9.84 x 8.3 x 8.3 inches (25 x 21 x 21 cm or) <b>Layer Thickness:</b> from 0.05 mm	STL, OBJ, 3MF	<ul style="list-style-type: none"> <li>• Consistently produces precise, high-quality, high-resolution prints</li> <li>• Supports multiple filament types enabling printing in a variety of materials</li> <li>• Reliable for printing simple and complex parts</li> <li>• Software auto-generates supports; minimal support removal and sanding required</li> </ul>
<b>Fused Deposition Modeling: FDM Printers (professional grade)</b>					
	<b>Stratasys Mojo</b>	<b>Plastic:</b> Acrylonitrile-Butadiene-Styrene+ (ABS+)	<b>Build Volume:</b> 5 x 5 x 5 inches (12.7 x 12.7 x 12.7 cm) <b>Layer Thickness:</b> 0.178 mm (0.007 in)	STL	<ul style="list-style-type: none"> <li>• High-quality strength and resolution for realistic prototypes or finished parts</li> <li>• Support material washes away enabling a smooth, clean finish without sanding or filing</li> </ul>
	<b>Stratasys uPrint SE</b>	<b>Plastic:</b> Acrylonitrile-Butadiene-Styrene+ (ABS+) <b>Color:</b> Ivory	<b>Build Volume:</b> 8 x 6 x 6 inches (203 x 152 x 152 mm) <b>Layer Thickness:</b> 0.254 mm (0.010 in)	STL	<ul style="list-style-type: none"> <li>• High-quality strength and resolution for realistic prototypes or finished parts</li> <li>• Support material washes away enabling a smooth, clean finish without sanding or filing</li> </ul>

Stereolithography: SLA Printers					
	<p><b>FormLabs Form 1+</b> <i>Laser-based: 405nm violet</i></p>	<p><b>Liquid Resin:</b> Methacrylate Photopolymer Resin</p> <p><b>Resin Types:</b> Rigid, Castable, High-temperature</p>	<p><b>Build Volume:</b> 4.9 × 4.9 × 6.5 inches (125 × 125 × 165 mm)</p> <p><b>Layer Thickness:</b> 25, 50, 100 microns (0.001, 0.002, 0.004 in)</p> <p><b>Minimum Feature Size:</b> 300 microns (0.012 in)</p>	<p>STL, OBJ</p>	<ul style="list-style-type: none"> <li>• Smooth, clean finish on any part</li> <li>• Variety of materials enable builds of rigid, flexible, and castable parts</li> <li>• Software auto-generates required supports; minimal post-processing, support removal and sanding required</li> <li>• UV lightbox enhances curing</li> </ul>
PolyJet Printers					
	<p><b>Stratasys Objet30 Prime</b></p>	<p><b>Multiple Materials:</b> Rigid (Vero), Rubber-like (Tango), High-temperature, Simulated Polypropylene</p> <ul style="list-style-type: none"> <li>• All materials not available at all times</li> </ul>	<p><b>Build Volume:</b> 11.57 x 7.55 x 5.85 inches (294 x 192 x 148.6 mm)</p> <p><b>Layer Thickness:</b> 28 microns (0.0011 in) for Tango materials; 16 microns (0.0006 in) for all other materials</p> <p><b>Accuracy:</b> 0.1mm (0.0039 in)</p> <p><b>Resolution:</b> x, y: 600 dpi; z: 1600 dpi</p> <p><b>Three build modes:</b></p> <ul style="list-style-type: none"> <li>• Draft (36 micron)</li> <li>• High Speed (28 micron)</li> <li>• High Quality (16 micron)</li> </ul>	<p>STL</p>	<ul style="list-style-type: none"> <li>• Prints precise consumer-product prototypes with smooth surfaces and flexible components</li> <li>• Rubber material enables prototyping of gaskets, plugs and seals</li> <li>• Offers rigid materials in multiple opaque shades as well as clear, for detail visualization and prototypes that include see-through components</li> <li>• Rubberlike materials for soft-touch features and flexible components</li> <li>• Capable of printing specialized materials such as High Temperature, Simulated Polypropylene and even Bio-compatible for medical device prototyping and production parts such as surgical guides</li> </ul>
Composite Printers					
	<p><b>Markforged Mark Two Professional</b> <i>Fused Filament Fabrication (FFF); Composite Filament Fabrication (CFF)</i></p>	<p><b>Base Material:</b> Nylon (extruded)</p> <p><b>Composite Infill:</b> Carbon Fiber, Fiberglass, Kevlar®</p>	<p><b>Build Volume:</b> 12.6 x 5.2 x 6.06 inches (320 x 132 x 154 mm)</p> <p><b>Layer Thickness:</b> FFF Printing: 100 Microns (0.1mm)</p>	<p>STL</p>	<ul style="list-style-type: none"> <li>• Capable of producing tough, abrasion-resistant, composite-reinforced parts</li> <li>• Carbon fiber material is 20x stiffer than ABS, making it useful for fixtures, jigs, and parts that need the highest strength-to-weight ratio</li> <li>• Kevlar® filament is perfect for parts that need to be stiff and tough</li> <li>• Fiberglass filament provides impressive strength, but at a lower cost than carbon</li> </ul>
	<p><b>Markforged Mark X</b> <i>Fused Filament Fabrication (FFF); Composite Filament Fabrication (CFF)</i></p>	<p><b>Base Material:</b> Onyx (extruded)</p> <p><b>Composite Infill:</b> Carbon Fiber, Fiberglass, Kevlar®</p>	<p><b>Build Volume:</b> 12.9 x 9.8 x 7.8 inches (330 x 250 x 200 mm)</p> <p><b>Layer Thickness:</b> FFF Printing: 50 Microns (0.05mm)</p>	<p>STL</p>	<ul style="list-style-type: none"> <li>• Prints larger parts with the high-strength materials</li> <li>• Onyx material combines nylon with micro-carbon reinforcement; 1.4 times stronger &amp; stiffer than ABS</li> <li>• Add carbon, Kevlar® and fiberglass filaments for additional strength</li> <li>• High quality finish; high heat tolerance</li> <li>• Laser displacement sensor enables in-process part inspection</li> </ul>

Colorjet Printers					
	<b>3D Systems</b> <b>ProJet CJP 260Plus</b>	<b>Material:</b> VisiJet PXL Core VisiJet PXL Clear Binder  <b>Colors:</b> Full color (CMY)	<b>Build Volume:</b> 9.3 x 7.3 x 5 inches (236 x 185 x 127 mm)  <b>Layer Thickness:</b> 0.004 in (0.1 mm)  <b>Resolution:</b> 300 x 450 dpi	STL, 3DS, VRML + more	<ul style="list-style-type: none"> <li>• Builds realistic, high definition, full-color concept models, assemblies and prototypes in full CMY color</li> <li>• Well-suited for concept modeling of communication, sales and marketing models; rapid design iteration; display/art models</li> <li>• Easy post-processing with no supports to remove</li> <li>• Choose from a range of part finishing options to meet your application requirements</li> </ul>
3D Scanner			Accuracy	Exports to:	General Features
	<b>NextEngine 3D Scanner HD</b>		0.005 inch accuracy	OBJ, STL, VRML + more	<ul style="list-style-type: none"> <li>• Captures fine detail to 100 micron precision</li> <li>• Provides higher point throughput and much better data fidelity</li> </ul>