

Eric Pitman Summer Workshop in Computational Science



2. Data Structures: Vectors and Data Frames



CENTER FOR **COMPUTATIONAL RESEARCH**

UB **University at Buffalo**
The State University of New York

Data Objects in R


These objects, composed of multiple atomic data elements, are the bread and butter of R:

- Vectors
- Data Frames



Vector Data Object

A vector is a list of elements having the *same type*.



Construct a Vector Data Object

	a
1	5
2	6
3	7
4	8

Use the `c()` function:

```
> a <- c(5,6,7,8) # vector with 4 numeric values
```

```
> d <- c("red", "orange", "green") # character vector
```

Accessing Vector Data

	d
1	"red"
2	"orange"
3	"green"

	a
1	5
2	6
3	7
4	8

Access by index or range:

> d[1] # retrieves "red"

> a[3] # retrieves 7

> d[1:2] # retrieves "red", "orange"

Element numbering starts at 1 in R

Information about a Vector

	y
1	3
2	5
3	7
4	9

> y <- c(3,5,7,9) # vector with 4 numeric values

> length(y) # how many elements?

> class(y) # class of a vector object is the class
of its elements

Information about a Vector

	y
1	3
2	5
3	7
4	9

> str(y)

structure of the vector: number of
elements, type, and contents

num [1:4] 3 5 7 9

Type of elements

Number (and positions) of elements

contents

Some Operations on Vectors

- `sum()` # Sum of all element values
- `length()` # Number of elements
- `unique()` # Generate vector of distinct values
- `diff()` # Generate vector of first differences
- `sort()` # Sort elements, omitting NAs
- `order()` # Sort indices, with NAs last
- `rev()` # Reverse the element order
- `summary()` # Information about object contents

Repercussions of NA

Any arithmetic operation on a structure containing an NA generates NA!

NA means “no value known”

```
> y = c(1, NA, 3, 2, NA)
```

```
> sum(y)
```

```
[1] NA
```

We must *remove NAs* to make calculations. How?



Finding NAs in a Data Structure

```
> y = c(1, NA, 3, 2, NA)
```

```
> summary(y)
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.	NA's
1.0	1.5	2.0	2.0	2.5	3.0	2



Handling Missing Data

Remove NAs prior to calculation:

```
> y = c(1, NA, 3, 2, NA) # [1, ?, 3, 2, ?]  
sum(y, na.rm=TRUE)      # removes NAs, then sums  
[1] 6                   # sum of 1 + 3 + 2
```

rm = "remove"



Data Frames



- A data frame is a structure consisting of columns of *various modes* (numeric, character, etc).
- Its rows and columns can be named.
- Data frames are handy containers for experimental data.

Data Frame Example



Data frames are handy containers for data that describe experimental subjects.

Student population data:

	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Constructing a Data Frame

1. Construct the vectors that hold column data:

```
height = c(68, 75, 60) # inches
```

```
age = c(16, 17, 16) # years
```

```
handed = c("L", "R", "R") # dominant hand: R=right, L=left
```

2. Construct the data frame by associating the columns:

```
data = data.frame(Height=height,  
                  Age=age,  
                  Hand=handed)
```

Name of the column!



Data Frame

Organized in rows and columns:



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Rows

Columns (formed from vectors)

Accessing by Index



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

First index is row, second index is column:

```
> data[1,1] # retrieves subject A's Height
```


Accessing by Index



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

```
> data[1, ] # retrieves all subject A data
```

```
  Height Weight Age Hand  
A     68   120  16   L
```

Comma is a placeholder in the [row, column] notation

Accessing by Index



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Comma is a placeholder in the [row, column] notation

```
> data[,1] # retrieves all Height data  
[1] 68 75 60
```

Accessing by Index



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

```
> data[1, ] # retrieves all subject A data
```

```
  Height Weight Age Hand  
A    68   120  16   L
```

```
> data[,1] # retrieves all Height data
```

```
[1] 68 75 60
```

Comma is a placeholder in the [row, column] notation

Try it: Accessing by Index



- > source("data-frame-simple-example.R")
- > data[2,3] # retrieves subject B's Age
- > data[2,] # retrieves all subject B data
- > data[,3] # retrieves all Age data

Accessing by Name



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

First is row, second is column:

```
> data["A","Height"] # retrieves subject A's Height  
# Notice the quotes!
```

Accessing by Name



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

```
> data["A", ] # retrieves all subject A data.  
# Notice the comma!
```

Accessing by Name



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

To fetch Height column:

```
> data[ , "Height"] # Notice the comma
```

Accessing by Name



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Another way to fetch Height column:

```
> data$Height
```


Try it: Accessing by Name



- > source("data-frame-simple-example.R")
- > data["B", "Age"] # retrieves B's Age
- > data["B",] # retrieves all B data
- > data\$Age # retrieves all Age data

Conditional Access



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Subjects who are taller than 65 inches:

```
> data[data$Height > 65, ] # subset of the data frame  
# (notice the comma!)
```

Conditional Access



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Heights over 65 inches:

```
> data$Height[data$Height > 65] # subset of a column  
# of the data frame
```

Conditional Access



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Heights equal to 75 inches:

```
> data$Height[data$Height == 75] # subset of a column  
# of the data frame
```

Try it: Conditional Access



```
> source("data-frame-simple-example.R")
```

```
# subset of the data frame having age<17 years:
```

```
> data[data$Age < 17, ]
```

```
# subset of a column of data frame, age<17 years:
```

```
> data$Age[data$Age < 17]
```

Conditional Access 2



	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

Heights over 65 inches:

```
> data[which(data$Height > 65), "Height"]
```

```
> subset(data, Height>65, select="Height")
```

handy if you have NAs in the dataframe.

Conditional Access 2: which()

	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

```
> which(data$Height > 65)
```

```
1 2
```

which() returns the indices for which the conditional is true!

Conditional Access 2: subset()

	Height	Weight	Age	Hand
A	68	120	16	L
B	75	160	17	R
C	60	118	16	R

```
> subset(data, Height>65, select="Height")
```

```
# subset() arguments are:
```

```
#           dataset to subset,  
#           subsetting condition to apply,  
#           columns to return
```


Data Frame Information

```
str(data)      # structure  
dim(data)     # dimensions  
is.data.frame(data) # returns a logical value
```

```
View(data)     # open View window of data  
head(data)    # beginning of the data frame  
tail(data)    # end of the data frame
```

```
names(data)    # names of the columns  
rownames(data) # names of the rows  
colnames(data) # names of the columns
```

```
> class(data)  
[1] "data.frame"
```

Student Dataset Example



Let's create our own dataset and put it in an R data frame:

- `FirstInitial`
- `LastInitial`
- `School`
- `Height`
- `HtUnit`
- `Age`
- `Handed`
- `Gender`

Student Dataset Example



Now we can write some R to select subsets of our data. Examples:

- How many students younger than 17?
- List heights of students at Williamsville North
- Genders of left-handers?

Interlude

Complete vector/data frame exercises.



Open in the RStudio source editor:

`<workshop>/exercises/exercises-vectors-matrices-dataframes.R`